

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 July 2003 (03.07.2003)

PCT

(10) International Publication Number
WO 03/054416 A1

(51) International Patent Classification⁷: **F16G 3/02**

(21) International Application Number: **PCT/CA01/01784**

(22) International Filing Date:
10 December 2001 (10.12.2001)

(25) Filing Language: **English**

(26) Publication Language: **English**

(71) Applicant: **LIPPERT PINTLEPIN MFG. INC.**
[CA/CA]; 6410, Fontaine, Rock-Forest, Québec J1N 2S6
(CA).

(72) Inventors: **CORRIVEAU, André**; 6410, Fontaine,
Rock-Forest, Québec J1N 2S6 (CA). **CRÊTE, Sylvain**; 20
Principale, Sawyerville, Québec J0B 3A0 (CA). **FRASER,**
Caroline; 65, rue de London, Sherbrooke, Québec J1H
3M4 (CA). **PLANTE, Jean-Sébastien**; 477, Bouchette,
Sherbrooke, Québec J1J 2T2 (CA).

(74) Agent: **ROBIC**; 55, St-Jacques, Montréal, Québec H2Y
3X2 (CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN,
YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **SPIRAL FOR INTERCONNECTING ENDS OF ENDLESS BELT SEGMENTS**



(57) Abstract: A spiral for interconnecting ends of endless belt segments with terminal fabric loops using a pintle. The spiral comprises a series of loops (2) having inverted U-shaped loop portions (4) extending in a transverse direction (6) of the spiral. The loop portions (4) have legs (8, 10) spaced apart from each other for passage of the pintle therebetween, and uppermost heads bending from and extending between the legs (8, 10). U-shaped loop linking portions (12) extend diagonally with respect to a longitudinal direction (7) of the spiral, between lower ends of the legs (8, 10) of successive loops. The loop portions (4) are parallel with and spaced from one another by a definite pitch distance (14) matching with the fabric loops and adapted to define openings (17) for interdigitation with a like spiral to form a channel (19) for the pintle without longitudinal deformation of the spirals during the interdigitation.

WO 03/054416 A1

SPIRAL FOR INTERCONNECTING ENDS OF ENDLESS BELT SEGMENTS**FIELD OF THE INVENTION**

The present invention relates to a spiral for interconnecting ends of endless belt segments.

BACKGROUND

Segments of an endless belt have ends provided with sets of terminal fabric loops interdigitatable with one another so that the segments can be connected together by insertion of a pintle into the channel formed by the interdigitated sets of loops of two adjacent belt segments. The sets of loops and the pintle are however subjected to high stresses and strains during operation of the endless belt, so their design and strength are of utmost importance as a loose segment or pintle may cause important damages to the machine or serious injuries to a passer-by.

The sets of loops are frequently provided by spirals seamed at the ends of the belt segments. US patent no. 5,915,422 (Fagerholm) shows an example of such a spiral attached at the end of a woven (felt) belt. When viewed sideways, the spiral exhibits a series of V-shaped loops spaced from one another by straight sections especially intended to receive flat filament yarns for attachment of the spiral to the end of the belt section. The interdigitation of two such spirals at the ends of adjacent belt sections is however uneven and unsteady due to the mismatching of the loops between the two interdigitated sets and the large spaces left between the loops for the yarns. Furthermore, the interdigitation is frequently incomplete or partial as a result of the non-complementary shapes of the spirals, so the resulting channel has a reduced size compared to the size of the loops and thus only a small size pintle can

disadvantageously be used instead of a larger size one. Furthermore, the pintle is prone to jam in or to deviate out of the channel due to its unevenness and irregularity.

US patents Nos. 4,539,730 (Romanski), 4,791,708 (Smolens), EP patent applications Nos. 0,275,656 (Gisourne) published on 27.07.88, 0,674,041 (Lorenz et al.) published on 27.09.95, and DE patent application No. 2,059,021 (Andrejewski et al.) published on 8.06.72 provide examples of spirals of the prior art. Each one of these spirals has its particular features for specific purposes, e.g. straight securing portions for improving the seam, interference fit to facilitate the joining of the spirals, etc. Yet, none of them can be made according to a monofilament diameter, a width, a height and especially a pitch, to fully meet the very requirements of the manufacturer's endless belts for which they are intended. As a result, they must be stretched or contracted during their assembly with the endless belts. Such longitudinal deformation makes the channel uneven and irregular with the aforesaid problems. It also increases the installation time and effort.

Also, spirals having a pitch of about two times the diameter of the monofilament are very difficult to make due to the shifting of the monofilament during the production of the spiral. No such spirals have apparently ever been successfully produced based on the teachings of the above patents. It is also worth mentioning that known manufactured spirals for interconnecting endless belt segments come in asymmetrical pair, i.e. left and right ones which cannot be interchanged and are also a cause of the aforesaid problems.

The currently known spiral designs are limited to a few models which in many cases are fairly unfit for the ever changing models of endless belt segments.

SUMMARY

An object of the invention is to provide a spiral for interconnecting ends of endless belt segments using a pintle, which better interdigitates with like spirals than the spirals of the prior art and which allows the use of a larger size pintle for interlocking the spirals together.

Another object of the invention is to provide such a spiral having loops that fully insert down to the bottom of a like spiral, and provide a fairly smooth and regular inner
10 channel facilitating the insertion of the pintle.

Another object of the invention is to provide such a spiral which can be easily manufactured in a large range of sizes and models to fit multiple needs and applications.

Another object of the invention is to provide such a spiral which can be made according to a required pitch for easier assembly with the endless belt, with the pitch possibly ranging over twice the diameter of the monofilament used to form the spiral.

According to the present invention, there is provided a
20 spiral for interconnecting ends of endless belt segments with terminal fabric loops using a pintle. The spiral comprises a series of loops having preformed inverted U-shaped loop portions extending in a transverse direction of the spiral. The loop portions have front and rear parallel legs spaced apart from each other for passage of the pintle therebetween, and an uppermost head bending from and extending between the legs. Preformed U-shaped loop linking portions extend diagonally with respect to a longitudinal direction of the spiral, between lower ends of the front legs and lower ends
30 of the rear legs of the next loop portions respectively. The loop portions are parallel with and spaced from one another by a definite pitch distance in the longitudinal direction of the spiral, adapted to match with the fabric loops at the ends of the endless belt segments and to define openings for

interdigitation with a like spiral to form a channel for the pintle without longitudinal deformation of the spirals during interdigitation.

Each loop portion may have projections made out of the spiral on opposite sides of the loop portion in the longitudinal direction of the spiral, for interlocking with like projections on the like spiral.

Preferably, the heads and the loop linking portions have substantially straight portions, so that the channel has a
10 cross-section more rectangular than oblong.

The spiral according to the invention almost fully blends with a like spiral, which leaves more inner space for a larger pintle or for receiving a filling material, while facilitating the spiral assembly.

According to the present invention, there is also provided a process for producing the spiral, characterized in that a monofilament made of a thermoformable material is wound around a rod having a cross-section reflecting a desired inner shape of the spiral. The wound monofilament is
20 press-shaped against the rod so that it forms a series of loops having the aforesaid features. The press-shaped monofilament is subjected to a heating and cooling fixating cycle.

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of preferred embodiments will be given herein below with reference to the following drawings, in which like numbers refer to like elements:

Figures 1A-B are front and side elevation views of a spiral according to the invention;

30 Figures 2A-C are front and side elevation and top views of a spiral with interlocking heads according to the invention;

Figure 3 is a perspective view illustrating a spiral according to the invention; and

Figure 4 is a side elevation view illustrating two spirals with interlocking heads during interdigitation in order to interconnect ends of endless belt segments.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figures 1A-B and 3, there is shown a spiral according to the invention, for interconnecting ends of endless belt segments with terminal fabric loops using a
10 pintle (not shown in the Figures). The spiral comprises a series of loops 2 each having a preformed inverted U-shaped loop portion 4 extending in a transverse direction of the spiral, as depicted by arrow 6 in Figure 3.

The loop portion 4 has front and rear parallel legs 8, 10 spaced apart from each other for passage of the pintle therebetween, as best shown in Figure 3. The loop portion 4 has also an uppermost head 18 bending from and extending between the legs 8, 10.

Each loop 2 also has a preformed U-shaped loop linking
20 portion 12 extending diagonally with respect to a longitudinal direction 7 of the spiral, between a lower end of the front leg 8 of the loop portion 4 and a lower end of a rear leg 10 of a loop portion 4 of a next one of the loops 2. The loop portions 4 are parallel with and spaced from one another by a definite pitch distance 14 in the longitudinal direction 7 of the spiral, adapted to match with the fabric loops at the ends of the endless belt segments and to define openings 17 for interdigitation with a like spiral to form a
30 channel 19 for the pintle, as best shown in Figure 4, without longitudinal deformation (stretching or contracting) of the spirals during the interdigitation. As there is no deformation, the interdigitation and assembly with the

endless belt segments are quite simple and easy, and the original dimensional and formal features of the spirals are preserved without any spatial or structural losses. Also, the inner channel 19 is thus fairly if not fully smooth and even, which facilitates the insertion of the pintle. Due to its symmetry, there is no longer any need for a left and right spiral model.

The series of loops 2 can be made of a monofilament (single wire) of polyester (trademark), nylon (trademark),
10 PEEK (PolyEther Ether Ketone), PVDS (Fluoropolymer), Ryton (trademark), or any other suitable material. A thread can also be used instead of a monofilament if desired. For interconnection of belt segments in paper industries, a polyester that resists to hydrolysis should preferably be used. For interconnection of belt segments in food industries, an atoxic material should be used. The monofilament may have a flat cross-section, providing more inner space for the channel 19. The spirals according to the invention can be seamed or otherwise attached to the ends of
20 the belt segments to be interconnected with yarns woven in the belt segments and curling back around the linking portions 12, forming the aforesaid terminal fabric loops. Without further alteration, the loop and linking portions 4, 12 have a uniform cross-section as illustrated in Figures 1A-B and 3.

Referring to Figures 2A-C, each loop portion 4 may have projections 22 made out of the spiral on opposite sides of the loop portion 4 in the longitudinal direction 7 of the spiral, for interlocking with like projections 22 on the like
30 spiral as exemplified in Figure 4. The projections 22 can be made by a flattening of the head 18 between the legs 8, 10 of each loop portion 4, provided that the monofilament has a cross-section (e.g. a round cross-section) suitable for the flattening operation which involves no injection of

additional material. As shown in Figure 2B, the heads 18 have a flared profile with bent surfaces 24 between the heads and the legs 8, 10 as a result of the flattening operation. As shown in Figure 2C, the heads 18 preferably have an oval shape when viewed from above. Such an interlocking feature is particularly useful to hold back the spirals together the time to install the pintle inside the channel 19. This feature along with the design of the spirals also prevent cross disengagement of the loops of the spirals if they are subjected to a contracting force. However, a loss in the strength of the resulting interconnection is likely to happen due to the flattening of the wire to form the heads 18 when made in this way.

Referring to Figures 1A-B and 3, the legs 8, 10 of each loop portion 4 may be longer than a width 16 of the loop portion 4 in the transverse direction 6 of the spiral, so that the channel 19 has an obround cross-section adapted to receive a flat pintle. Furthermore, the heads 18 and the loop linking portions 12 preferably have substantially flat inner faces 26 so that the channel 19 has a cross-section more rectangular than oblong. Such a feature may especially be difficult to achieve for smaller sizes of spirals due to the bending of the material, yet more channel space is nevertheless obtained compared to conventional spirals.

Referring to Figure 4, typical sizes (or models) of spirals made according to the invention are 5.2 mm (height) x 2.6 mm (transverse width of a loop 2), 3.7 mm x 2.2 mm, and .38 mm x .63 mm. Larger or smaller sizes can also be considered, provided that the loop per spiral rate is adjusted accordingly. The gauge of the wire used to make the spiral can be chosen according to the needs (desired strength, available space for the spiral, etc.). The design of the spirals according to the invention allows two interdigitated spirals to reach the bottom of the other. With

the larger channel 19 obtained with the spirals according to the invention, a larger (stronger) pintle can be used, or a remaining gap in the channel 19 after pintle insertion can be filled with a suitable material.

Typical pitch distances 14 with the spiral according to the present invention range from one time to at least twice a diameter of the material used to form the spiral. Thus, the very requirements specified by the client can be met. In fact, contrary to the limited number of physical
10 characteristics that a client is used to specify when ordering conventional types of spirals, the following parameters can be specified for the manufacture of the spirals according to the present invention: the type of spiral (regular or with teeth); the material; the diameter of the monofilament; the dimensions of the monofilament; the spiral dimensions (width x thickness); the number of pitch of the spiral / 100 mm (or another predetermined spiral length). Thus, the spirals according to the present invention fully match with the endless belt segments and their terminal
20 loops, instead of deforming the spirals to match the terminal loops of the endless belt segments or stretching the terminal loops to match the spirals as in the conventional practice, with all the problems related to such practice. The pitch of the spirals according to the present invention can be chosen so that more than one yet a definite number of terminal loops hook around each loop linking portion 12 of the spirals.

The spiral can advantageously be produced using a monofilament made of thermoformable material. The monofilament is first wound around a rod (not shown in the
30 Figures) having a cross-section reflecting a desired inner shape of the spiral (i.e. to form the channel 19). The wound monofilament is press-shaped against the rod so that it forms a series of loops 2 having the above described features. The

press-shaped monofilament is then subjected to a heating and cooling fixating cycle.

While embodiments of this invention have been illustrated in the accompanying drawings and described above, it will be evident to those skilled in the art that changes and modifications may be made therein without departing from the essence of this invention. All such modifications or variations are believed to be within the scope of the invention as defined by the claims appended hereto.

CLAIMS:

1. A spiral for interconnecting ends of endless belt segments with terminal fabric loops using a pintle, comprising a series of loops (2) each having a preformed inverted U-shaped loop portion (4) and a preformed U-shaped loop linking portion (12), characterized in that:

the preformed inverted U-shaped loop portion (4) extends in a transverse direction (6) of the spiral, the loop portion
10 (4) having front and rear parallel legs (8, 10) spaced apart from each other for passage of the pintle therebetween, and an uppermost head (18) bending from and extending between the legs (8, 10), the front and rear legs (8, 10) having lower ends; and

the preformed U-shaped loop linking portion (12) extends diagonally with respect to a longitudinal direction (7) of the spiral, between the lower end of the front leg (8) of the loop portion (4) and a lower end of a rear leg (10) of a loop portion (4) of a next one of the loops (2), the loop portions
20 (4) being parallel with and spaced from one another by a definite pitch distance (14) in the longitudinal direction (7) of the spiral adapted to match with the fabric loops at the ends of the endless belt segments and to define openings (17) for interdigitation with a like spiral to form a channel (19) for the pintle without longitudinal deformation of the spirals during the interdigitation.

2. The spiral according to claim 1, characterized in that at least the loop linking portion (12) and the legs (8,
30 10) of the loop portion (4) have a uniform cross-section.

3. The spiral according to claim 2, characterized in that the heads (18) and the loop linking portions (12) have

substantially straight portions, so that the channel (19) has a cross-section more rectangular than oblong.

4. The spiral according to claim 2, characterized in that the head (18) of each loop portion has projections (22) made out of the spiral on opposite sides of the loop portion (4) in the longitudinal direction (7) of the spiral, for interlocking with like projections on the like spiral.

10 5. The spiral according to claim 2, characterized in that the series of loops (2) are made of a monofilament having a flat cross-section.

6. The spiral according to claim 3, characterized in that the series of loops (2) are made of a monofilament having a round cross-section.

7. The spiral according to claim 4, characterized in that the series of loops (2) are made of a monofilament
20 having a round cross-section.

8. The spiral according to claim 7, characterized in that the projections of the heads (18) are made by flattening of the monofilament between the legs (8, 10) of each loop portion (4).

9. The spiral according to claim 8, characterized in that the heads (18) have an oval shape when viewed from above.
30

10. The spiral according to claim 8, characterized in that the heads (18) have a flared profile with bent surfaces between the heads and the legs (8, 10).

11. The spiral according to claim 2, characterized in that the series of loops (2) are made of a monofilament of polyester, nylon, polyether ether ketone, or a fluoropolymer.

12. The spiral according to claim 2, characterized in that the series of loops (2) are made of a monofilament of an atoxic polyester.

13. The spiral according to claim 2, characterized in
10 that the series of loops (2) are made of a monofilament of hydrolysis-resistant polyester.

14. The spiral according to claim 2, characterized in that the pitch distance (14) ranges from one time to at least twice a diameter of a monofilament forming the spiral.

15. A spiral for interconnecting ends of endless belt segments with terminal fabric loops using a pintle, comprising a monofilament made of a thermoformable material,
20 and characterized in that the monofilament is wound around a rod having a cross-section reflecting a desired inner shape of the spiral;

the wound monofilament is press-shaped against the rod so that the monofilament forms a series of loops (2) each having:

an inverted U-shaped loop portion (4) extending in a transverse direction (6) of the spiral, the loop portion (4) having front and rear parallel legs (8, 10) spaced apart from each other for passage of the pintle therebetween, and an uppermost head (18) bending from
30 and extending between the legs (8, 10), the front and rear legs (8, 10) having lower ends; and

a U-shaped loop linking portion (12) extending diagonally with respect to a longitudinal direction (7)

of the spiral, between the lower end of the front leg (8) of the loop portion (4) and a lower end of a rear leg (10) of a loop portion (4) of a next one of the loops (2), the loop portions (4) being parallel with and spaced from one another by a definite pitch distance (14) in the longitudinal direction (7) of the spiral adapted to match with the fabric loops at the ends of the endless belt segments and to define openings for interdigitation with a like spiral to form a channel (19) for the pintle without longitudinal deformation of the spirals during the interdigitation; and
the press-shaped monofilament is subjected to a heating and cooling fixating cycle.

16. A process for producing a spiral for interconnecting ends of endless belt segments with terminal fabric loops using a pintle, characterized in that it comprises:

wounding a monofilament made of a thermoformable material around a rod having a cross-section reflecting a desired inner shape of the spiral;

press-shaping the wound monofilament against the rod so that the monofilament forms a series of loops (2) each having:

an inverted U-shaped loop portion (4) extending in a transverse direction (6) of the spiral, the loop portion (4) having front and rear parallel legs (8, 10) spaced apart from each other for passage of the pintle therebetween, and an uppermost head (18) bending from and extending between the legs (8, 10), the front and rear legs (8, 10) having lower ends; and

a U-shaped loop linking portion (12) extending diagonally with respect to a longitudinal direction (7) of the spiral, between the lower end of the front leg (8) of the loop portion (4) and a lower end of a rear

leg (10) of a loop portion (4) of a next one of the loops (2), the loop portions (4) being spaced from one another by a definite pitch distance in the longitudinal direction (7) of the spiral adapted to match with the fabric loops at the ends of the endless belt segments and to define openings for interdigitation with a like spiral to form a channel (19) for the pintle without longitudinal deformation of the spirals during the interdigitation; and

- 10 subjecting the press-shaped monofilament to a heating and cooling fixating cycle.

1/4




FIG. 1A




FIG. 1B




FIG. 2A

2/4

FIG. 2B




FIG. 2C

3/4




FIG. 3

4/4




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 01/01784

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16G3/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16G D21F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, WPI Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	WO 01 96761 A (LIPPERT PINTLEPIN MFG INC) 20 December 2001 (2001-12-20) page 3, line 20 -page 4, line 34; figures 1-4	1,2,4,5, 7,8,11, 12
X	US 4 539 730 A (ROMANSKI ERIC R) 10 September 1985 (1985-09-10) cited in the application column 2, line 61 -column 3, line 49; figures 1-5	1,2,4, 7-9,11, 14
Y		15,16
A		6,7
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

8 July 2002

Date of mailing of the international search report

16/07/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Baron, C

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 364 066 A (ASTEN GROUP) 18 April 1990 (1990-04-18) column 4, line 15 -column 5, line 28; figures 1-8	1,15,16
A	---	5
X	EP 0 674 041 A (ASTEN INC) 27 September 1995 (1995-09-27) cited in the application column 3, line 35 -column 4, line 13; figures 1-4	1
A	---	15,16
X	DE 20 59 021 A (OPTI-HOLDING) 8 June 1972 (1972-06-08) cited in the application page 6, line 1 - line 28; figures 1-3	1,2,4
A	---	15,16
Y	US 4 791 708 A (SMOLENS H DANA) 20 December 1988 (1988-12-20) cited in the application column 5, line 61 -column 6, line 7; figures 1,3	15,16
A	---	11-13
	EP 0 967 306 A (JOHNS MANVILLE INT INC) 29 December 1999 (1999-12-29) page 1, line 3 - line 5 page 2, line 39-42 page 5, line 19 - line 20	
A	---	
	EP 0 275 656 A (SCAPA PORRITT LTD) 27 July 1988 (1988-07-27) cited in the application	
A	---	
	US 5 915 422 A (FAGERHOLM LARS) 29 June 1999 (1999-06-29) cited in the application	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 01/01784

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0196761 A	20-12-2001	AU 5808301 A WO 0196761 A1 US 2002056174 A1	24-12-2001 20-12-2001 16-05-2002
US 4539730 A	10-09-1985	AT 387046 B AT 183084 A AU 564120 B2 AU 2353684 A BE 900395 A1 BR 8401447 A CA 1231574 A1 CA 1254725 A2 DE 3420547 A1 DE 3448581 C2 ES 535319 D0 ES 8605066 A1 FI 843253 A ,B FR 2551105 A1 GB 2145367 A ,B IT 1208668 B JP 60048702 A MX 168991 B MX 157467 A NL 8401080 A NO 843280 A ,B, NZ 206885 A SE 463107 B SE 8404097 A US 4649619 A ZA 8400319 A	25-11-1988 15-04-1988 30-07-1987 28-02-1985 17-12-1984 11-06-1985 19-01-1988 30-05-1989 07-03-1985 25-05-2000 01-03-1986 01-08-1986 23-02-1985 01-03-1985 27-03-1985 10-07-1989 16-03-1985 16-06-1993 18-11-1988 18-03-1985 25-02-1985 10-09-1986 08-10-1990 23-02-1985 17-03-1987 29-08-1984
EP 0364066 A	18-04-1990	US 4862926 A AT 99365 T AU 606522 B2 AU 3493889 A CA 1320066 A1 CA 1329502 A1 DE 68911839 D1 DE 68911839 T2 EP 0364066 A1 NZ 229117 A NZ 235990 A	05-09-1989 15-01-1994 07-02-1991 26-04-1990 13-07-1993 17-05-1994 10-02-1994 19-05-1994 18-04-1990 29-01-1991 26-07-1991
EP 0674041 A	27-09-1995	US 5488976 A CA 2140193 A1 EP 0674041 A2	06-02-1996 17-09-1995 27-09-1995
DE 2059021 A	08-06-1972	DE 2059021 A1	08-06-1972
US 4791708 A	20-12-1988	CA 1248799 A1	17-01-1989
EP 0967306 A	29-12-1999	DE 19828517 A1 EP 0967306 A1 US 6165614 A	30-12-1999 29-12-1999 26-12-2000
EP 0275656 A	27-07-1988	EP 0275656 A1 FI 875457 A GB 2201121 A ,B	27-07-1988 14-06-1988 24-08-1988

Form PCT/ISA/210 (patent family annex) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 01/01784

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0275656	A	US 4827579 A	09-05-1989
US 5915422	A	29-06-1999	
		SE 504119 C2	18-11-1996
		AT 201068 T	15-05-2001
		AU 688209 B2	05-03-1998
		AU 5166896 A	16-10-1996
		BR 9607970 A	13-01-1998
		CA 2216938 A1	03-10-1996
		CN 1179802 A , B	22-04-1998
		DE 69612742 D1	13-06-2001
		DE 69612742 T2	18-10-2001
		EP 0817883 A1	14-01-1998
		ES 2157433 T3	16-08-2001
		JP 11502902 T	09-03-1999
		NO 974377 A	24-11-1997
		NZ 304474 A	28-01-1999
		SE 9501074 A	28-09-1996
		WO 9630589 A1	03-10-1996
		ZA 9602445 A	03-10-1996

Form PCT/ISA/210 (patent family annex) (July 1992)

PUB-NO: WO003054416A1

DOCUMENT-IDENTIFIER: WO 3054416 A1

TITLE: **SPIRAL** FOR INTERCONNECTING ENDS OF ENDLESS **BELT**
SEGMENTS

PUBN-DATE: July 3, 2003

INVENTOR-INFORMATION:

NAME	COUNTRY
CORRIVEAU, ANDRE	N/A
CRETE, SYLVAIN	N/A
FRASER, CAROLINE	N/A
PLANTE, JEAN-SEBASTIEN	N/A

INT-CL (IPC): F16G003/02

EUR-CL (EPC): D21F001/00 ; F16G003/02

ABSTRACT:

CHG DATE=20031203 STATUS=O>A **spiral** for interconnecting ends of endless **belt** segments with terminal fabric loops using a **pintle**. The **spiral** comprises a series of loops (2) having inverted U-shaped loop portions (4) extending in a transverse direction (6) of the **spiral**. The loop portions (4) have legs (8, 10) spaced apart from each other for passage of the **pintle** therebetween, and uppermost heads bending from and extending between the legs (8, 10). U-shaped loop linking portions (12) extend diagonally with respect to a longitudinal direction (7) of the **spiral**, between lower ends of the legs (8, 10) of successive loops. The loop portions (4) are parallel with and spaced from one another by a definite pitch distance (14) matching with the fabric loops and adapted to define openings (17) for interdigitation with a like **spiral** to form a channel (19) for the **pintle** without longitudinal deformation of the **spirals** during the interdigitation.

----- KWIC -----

Abstract Text - FPAR (1):

CHG DATE=20031203 STATUS=O>A **spiral** for interconnecting ends of endless **belt** segments with terminal fabric loops using a **pintle**. The **spiral** comprises a series of loops (2) having inverted U-shaped loop portions (4) extending in a transverse direction (6) of the **spiral**. The loop portions (4) have legs (8, 10) spaced apart from each other for passage of the **pintle** therebetween, and uppermost heads bending from and extending between the legs (8, 10). U-shaped

loop linking portions (12) extend diagonally with respect to a longitudinal direction (7) of the spiral, between lower ends of the legs (8, 10) of successive loops. The loop portions (4) are parallel with and spaced from one another by a definite pitch distance (14) matching with the fabric loops and adapted to define openings (17) for interdigitation with a like spiral to form a channel (19) for the pintle without longitudinal deformation of the spirals during the interdigitation.

Title of Patent Publication - TTL (1):

SPIRAL FOR INTERCONNECTING ENDS OF ENDLESS BELT SEGMENTS